

Activity 2: Writing

Regardez la vidéo une nouvelle fois et compléter les blancs.

- 1) Use your tire iron to loosen the lug nuts on your tire.
- 2) Position the floor jack underneath [] car.
- 3) Once you have identified your safe jack points, [] the car high enough to place a [] [] underneath it.
- 4) Once the [] stand is positioned safely, [] the car onto the jack stand and [] the [] jack.
- 5) Now, you can finish removing the [] nuts from your [] set.
- 6) Next, [] your []
- 7) Now, you should be able to see your [] and the [] calliper [].
- 8) There are 2 [] located at the top and bottom of the interior side of the [] assembly. Using a [] wrench, [] these [].
- 9) At this point, you can [] the calliper [] from the [] revealing the [] [].
- 10) Now, that you can see the [] [], carefully remove them from the [].
- 11) Before you install your new [] [], you'll want to [] some brake [] to the [] of the pads.
- 12) Do not allow any [] to get on the [] of the [] or the [] directly.
- 13) Next, [] the brake pads in the same orientation as the ones you removed previously.
- 14) Now, you will need to [] the [] assembly to [] the new ticker [] pads. To do this, [] one of the old [] inside the [] assembly against the large circular []. Next, insert the [] tool and adjust it until it is taut between the calliper clamps. [] the brake tool handle until the [] has been fully pressed back into the calliper [].

- 15) Now, the [] assembly should fit over the brake [] you have just replaced.
- 16) Once the calliper assembly is back in place, [] the [] and hand [] them.
- 17) Next, come back with a [] wrench to [] them entirely.
- 18) You can now replace your tire on top of the wheel assembly and hand [] the [] nuts to keep them in place.
- 19) Once your [] is secure, place the jack [] underneath your vehicle again and [] it high enough to [] your [] stand.
- 20) [] your jack stand from underneath your vehicle and [] your car back down the ground.
- 21) Once your car is safely [] : [] you [] from beneath your vehicle.
- 22) Finally, [] your tire [] to [] all of your [] nuts securely. [] [] each lug nut individually to make sure they [] as tight as possible [] driving your vehicle.