

# PROCEDURE TEXT

Name:

Level:

| TEXT   | PART |
|--|------|
| New spark plug, Spark plug wrench, Cleaning cloth, Anti-seize lubricant (optional)   |      |
| <ol style="list-style-type: none"><li>1. Make sure the engine is turned off and cool before starting.</li><li>2. Use the spark plug wrench to remove the old spark plug from the engine.</li><li>3. Clean the area around the spark plug hole with a cleaning cloth to remove any debris.</li><li>4. Apply a small amount of anti-seize lubricant to the threads of the new spark plug (optional).</li><li>5. Install the new spark plug and tighten it with the spark plug wrench.</li><li>6. Start the engine to ensure it's running smoothly.</li></ol> |      |

How to Change a Motorcycle Spark Plug

| PARTS      | TEXT  |
|------------|---|
| Material   | How to Operate a Simple Drill Press   |
| Title/Goal |   |
| Steps      | <ol style="list-style-type: none"><li>1. Before starting, put on your safety goggles to protect your eyes.</li><li>2. Then, secure the workpiece on the drill press table using clamps.</li><li>3. After that, turn on the drill press and lower the drill bit onto the workpiece slowly.</li><li>4. Once the hole is drilled, turn off the machine and remove the workpiece carefully.</li></ol> <ul style="list-style-type: none"><li>• Drill press machine</li><li>• Safety goggles</li><li>• Workpiece (material to be drilled)</li></ul> |