




NAMA :

KELAS :



1. Silahkan ananda lengkapi perintah dibawah ini

```
Switch#conf
Switch#configure ter
Switch#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#
MLS(config)#vlan 10
MLS(config-vlan)#
MLS(config-vlan)#exit
MLS(config)#vlan 20
MLS(config-vlan)#name LAPTOP
MLS(config-vlan)#exit
MLS(config)#
MLS(config-if-range)#switchport mode access
MLS(config-if-range)#
MLS(config-if-range)#exit
MLS(config)#int range fa 0/3-4
MLS(config-if-range)#
MLS(config-if-range)#switchport access vlan 20
MLS(config-if-range)#exit
MLS(config)#
```





```
MLS(config-if)#
```

```
%LINK-5-CHANGED: Interface Vlan10, changed state to up
```

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan10, changed  
state to up
```

```
MLS(config-if)#ip address 192.168.100.254 255.255.255.0
```

```
MLS(config-if)#exit
```

```
MLS(config)#int vlan 20
```

```
MLS(config-if)#
```

```
%LINK-5-CHANGED: Interface Vlan20, changed state to up
```

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan20, changed  
state to up
```

```
MLS(config-if)#
```

```
MLS(config-if)#exit
```

```
MLS(config)#
```

```
MLS(config)#exit
```

```
MLS#
```

```
%SYS-5-CONFIG_I: Configured from console by console
```

```
MLS#
```

```
Destination filename [startup-config]?
```

```
Building configuration...
```

```
[OK]
```



