

A- Choose the correct modal verb



- 1- Put the rubber gloves and a face shield or the safety goggles. The fuel **can / must** be poisonous.
- 2- The chart provided in this section **needs / should** be used to augment the inspection.
- 3- A mechanical magnetic plug is installed in the casing. For the single engines, it is installed on the right of the reduction gearbox module. For the twin engines, it **can / must** be at either on the left or on the right of the reduction gearbox module according to the position of the engine on the airframe.
- 4- *NOTE:* The position of the marks is important: the M05 mark **should / must** be towards the reduction gearbox module, the M04 mark **may / must** be towards the power turbine module
- 5- The pilot **should / can** ensure that the proper grade of fuel and the proper additives, when required, are being dispensed.

B- COMPLETE WITH THE CORRECT MODAL VERB. DRAG AND DROP.

1-

SHOULD - CAN - MAY

Refueling of a turbine aircraft while the blades are turning, known as "hot refueling," _____ be practical for certain

types of operation. However, this _____ be hazardous if not properly conducted. Pilots _____ remain at the flight controls.

2-

MUST - MAY

Where high temperatures _____ exist during engine operation or after shutdown, fuel hoses _____ be capable of withstanding these temperatures.

C- Fill in the gaps: CAN – MUST – SHOULD - MAY

- 1- This inspection _____ be done before the next flight of the airplane.
- 2- High intensity lightning strike _____ cause problems to the electrical / electronic equipment. For example, wire shielding _____ be disturbed or degraded.
- 3- This procedure _____ be done as a follow-on program if initial damage was not found.
- 4- Airlines _____ insure the latest revisions of the standards and documents are applied.

5- Warning: if potable water system is not drained or in normal use., a minimum of one time each three days, the growth of bacteria _____ occur. If bacteria growth continues and you drink the water, illness _____ occur.

6- You _____ remove the pressure cap slowly. You _____ bleed the remaining pressure or the cap _____ come off with large force. Injury to persons and damage to equipment _____ occur

7- With two flat tires on one main gear, if it is possible, you _____ replace one of the flat tires with a serviceable tire before towing to prevent damage to the tires and wheels

