

## **Activity 2:** Writing

Regardez la vidéo une nouvelle fois et compléter les blancs.

- 1) Use your tire iron to loosen the lug nuts on your tire.
- 2) Position the floor jack underneath [ ] car.
- 3) Once you have identified your safe jack points, [ ] the car high enough to place a [ ] [ ] underneath it.
- 4) Once the [ ] stand is positioned safely, [ ] the car onto the jack stand and [ ] the [ ] jack.
- 5) Now, you can finish removing the [ ] nuts from your [ ] set.
- 6) Next, [ ] your [ ]
- 7) Now, you should be able to see your [ ] and the [ ] calliper [ ].
- 8) There are 2 [ ] located at the top and bottom of the interior side of the [ ] assembly. Using a [ ] wrench, [ ] these [ ].
- 9) At this point, you can [ ] the calliper [ ] from the [ ] revealing the [ ] [ ].
- 10) Now, that you can see the [ ] [ ], carefully remove them from the [ ].
- 11) Before you install your new [ ] [ ], you'll want to [ ] some brake [ ] to the [ ] of the pads.
- 12) Do not allow any [ ] to get on the [ ] of the [ ] or the [ ] directly.
- 13) Next, [ ] the brake pads in the same orientation as the ones you removed previously.
- 14) Now, you will need to [ ] the [ ] assembly to [ ] the new ticker [ ] pads. To do this, [ ] one of the old [ ] inside the [ ] assembly against the large circular [ ]. Next, insert the [ ] tool and adjust it until it is taut between the calliper clamps. [ ] the brake tool handle until the [ ] has been fully pressed back into the calliper [ ].

15) Now, the [ ] assembly should fit over the brake [ ] you have just replaced.

16) Once the calliper assembly is back in place, [ ] the [ ] and hand [ ] them.

17) Next, come back with a [ ] wrench to [ ] them entirely.

18) You can now replace your tire on top of the wheel assembly and hand [ ] the [ ] nuts to keep them in place.

19) Once your [ ] is secure, place the jack [ ] underneath your vehicle again and [ ] it high enough to [ ] your [ ] stand.

20) [ ] your jack stand from underneath your vehicle and [ ] your car back down the ground.

21) Once your car is safely [ ] : [ ] you [ ] from beneath your vehicle.

22) Finally, [ ] your tire [ ] to [ ] all of your [ ] nuts securely. [ ] [ ] [ ] each lug nut individually to make sure they [ ] as tight as possible [ ] driving your vehicle.